



# LOCKNUT THREAD SIZES – UNITED STATES FORM



LOCKNUT NUMBER	NUMBER THREADS PER INCH	PITCH DIAMETER		HELIX ANGLE	O.D.	
		MAXIMUM	MINIMUM		MAXIMUM	MINIMUM
N-00	32	.3707	.3681	1° 28'	.391	.3856
N-01	32	.4487	.4461	1° 16'	.469	.4636
N-02	32	.5657	.5627	0° 59'	.586	.5806
N-03	32	.6438	.6407	0° 53'	.664	.6586
N-04	32	.7607	.7573	0° 44'	.781	.7756
N-05	32	.9487	.9453	0° 36'	.969	.9636
N-06	18	1.1369	1.1329	0° 52'	1.173	1.1648
N-07	18	1.3399	1.3359	0° 45'	1.376	1.3678
N-08	18	1.5269	1.5224	0° 39'	1.563	1.5548
N-09	18	1.7309	1.7264	0° 35'	1.767	1.7588
N-10	18	1.9309	1.9264	0° 31'	1.967	1.9588
N-11	18	2.1209	2.1158	0° 28'	2.157	2.1488
N-12	18	2.3239	2.3188	0° 26'	2.360	2.3518
N-13	18	2.5119	2.5068	0° 24'	2.548	2.5398
N-14	18	2.7149	2.7098	0° 22'	2.751	2.7428
*AN-15	12	2.8789	2.8735	0° 31'	2.933	2.9218
*AN-16	12	3.0829	3.0770	0° 29'	3.137	3.1258
*AN-17	12	3.2859	3.2785	0° 27'	3.340	3.3288
*AN-18	12	3.4729	3.4655	0° 26'	3.527	3.5158
*AN-19	12	3.6759	3.6685	0° 24'	3.730	3.7188
*AN-20	12	3.8639	3.8565	0° 23'	3.918	3.9068
*AN-21	12	4.0679	4.0596	0° 22'	4.122	4.1108
*AN-22	12	4.2709	4.2626	0° 21'	4.325	4.3138
*AN-24	12	4.6619	4.6536	0° 19'	4.716	4.7048
*AN-26	12	5.0519	5.0436	0° 17'	5.106	5.0948
*AN-28	12	5.4429	5.4346	0° 16'	5.497	5.4858
*AN-30	12	5.8339	5.8256	0° 15'	5.888	5.8768
*AN-32	8	6.2028	6.1937	0° 22'	6.284	6.2688
*AN-34	8	6.5778	6.5687	0° 20'	6.659	6.6438
*AN-36	8	6.9848	6.9757	0° 19'	7.066	7.0508
*AN-38	8	7.3908	7.3817	0° 18'	7.472	7.4568
*AN-40	8	7.7658	7.7544	0° 17'	7.847	7.8318

THREADS ARE AMERICAN (NATIONAL) STANDARD FORM, FINE PITCH, EQUIVALENT TO A CLASS 3 FIT.

\*PREFIX "A" BEFORE LOCKNUT NUMBER, INDICATES THAT THIS SIZE WAS PREVIOUSLY MANUFACTURED WITH 11 THREADS PER INCH.